

Code	Designation
	<p><b>THB3A</b></p> <p><b>bulb &amp; capillary thermostat</b></p> <p>temperature range : <b>-35°C / +35°C</b>  max load : 16A 250V AC  sensor : <b>bulb</b> (2m length capillary)  degree of protection : IP44</p>
	<p><b>THI3A</b></p> <p><b>Atmosphere thermostat</b></p> <p>temperature range : <b>0°C / +60°C</b>  inside setting  max load : 15A 250V AC  degree of protection : IP65</p>
	<p><b>R40</b></p> <p><b>R40 temperature controller</b></p> <p>temperature range : <b>0°C / +40°C</b>  max load : 16A 250V AC  sensor : 3m length NTC  degree of protection : IP20</p>
	<p><b>THE3A</b></p> <p><b>THE3A temperature controller</b></p> <p>temperature range : <b>0°C / +60°C</b>  max load : 16A 250V AC  sensor : 2m length PTC  degree of protection : IP54</p>
	<p><b>THP3A</b></p> <p><b>THP3A temperature controller</b></p> <p>temperature range : <b>0°C / +60°C</b>  max load : 16A 250V AC  sensor : 1,5m length CTP  degree of protection : IP67</p> <p>hanging up handle</p>

DOC0591A